

display means for receiving display data from said control device and projecting a picture represented by said display data onto said display screen;

*a-22
cmd d*
input/output means connected to the control device and adapted for generating display control signals controlling said display means, said input/output means being further connectable to at least one external peripheral equipment to input/output data pertaining to supplementary information appended to input data; and

display control means for controlling a picture projected by said display means based on a display control signal input through said input/output means.--

*a-23
cmt*
--3. (Amended) The projection display apparatus according to claim 1 wherein an operating input device for generating an operating input signal as an external peripheral equipment is connected to said input/output means and wherein said display control means controls a picture projected by said display means in accordance with a pointer control signal from the control device based on the operating input signal generated in said operating input device.--

--4. (Amended) The projection display apparatus according to claim 1 wherein a second projection display apparatus is connected as an external peripheral device to said input/output means and wherein said input/output means outputs display data and display control signals to said second projection display apparatus.--

--5. (Amended) A projection display system in which a control device as a host and a projection display apparatus as a target controlled by said control device are interconnected over

a serial interface, and in which data transmission/reception is made bi-directionally at least between said control device and said projection display apparatus to project a picture by said projection display apparatus on a display screen, wherein

*a-23
could*

said projection display apparatus includes display means for receiving display data from said control device and projecting a picture represented by said display data onto said display screen, input/output means connected to the control device adapted for generating display control signals controlling said display means, said input/output means being further connectable to at least one external peripheral equipment to input/output data pertaining to supplementary information appended to input data, and display control means for controlling a picture projected by said display means based on a display control signal input through said input/output means, and wherein

said control device includes input/output means connected to the projection display apparatus and control means for outputting display control signals and display data to the projection display apparatus and to said external peripheral equipment connected to said projection display apparatus to cause the projection display apparatus to project a picture on the display screen.--

*a-24
cont*

--7. (Amended) The projection display system according to claim 5 wherein there is provided an operating input device connected as an external peripheral device to said input/output means of said projection display apparatus to generate an operating input signal, and wherein said display control means controls a picture projected by said display means on said display screen, in accordance with a pointer control signal from said control device which is based on the operating input signal generated in said operating input device.--

a-24
cndd

--8. (Amended) The projection display system according to claim 5 wherein said projection display apparatus is a first projection display apparatus, and a second projection display apparatus is connected as an external peripheral device to said input/output means of said first projection display apparatus and wherein the input/output means of said first projection display apparatus outputs display data and the display control signal from the control device to said second projection display apparatus.--

Please add the following claims 10-11:

a-25

--10. (New) The projection display apparatus according to claim 1, further comprising receiving means for receiving a remote control signal from a remote control device and providing a detection signal in response thereto, wherein said display control means outputs a pointer control signal to said display means to shift a pointer included in said picture projected by said display means responsive to said detection signal from said receiving means.--

--11. (New) The projection display system according to claim 5, wherein said projection display apparatus further comprises receiving means for receiving a remote control signal from a remote control device and providing a detection signal in response thereto, and said display control means outputs a pointer control signal to said display means to shift a pointer included in said picture projected by said display means responsive to said detection signal from said receiving means.--
